

RAINWATER HARVESTING TANK

MAKE USE OF RAINWATER AND

REDUCE YOUR NEED FOR MAINS



www.maxwellconcrete.co.uk



Maxwell Concrete

Maxwell Concrete
22 Folliard Road, Castlederg
Co Tyrone, BT81 7JW
T: 028 816 71326 F: 028 816 71736
Email: info@maxwellconcrete.co.uk

NEW PRODUCT! SEPTIC TANKS DELIVERED & PLACED INTO THE EXCAVATION

RAINWATER HARVESTING TANK

SAVE MONEY BY SAVING YOUR WATER

QUALITY:

- DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 5502 AND BS 8007
- FIBRE REINFORCED TO PREVENT FROST DAMAGE

DESIGN:

- THE TANK IS SUITABLE FOR RAINWATER STORAGE ONLY

TECHNICAL:

- BACKFILLING SHOULD NOT OCCUR TO FULL HEIGHT UNTIL AT LEAST THREE WEEKS AFTER CONSTRUCTION
- BEFORE INSTALLATION A SUB-FLOOR OF 150MM (6") IS RECOMMENDED
- LIFTING EQUIPMENT SHOULD BE SELECTED BY TAKING INTO ACCOUNT THE UNIT WEIGHT, DIMENSIONS AND THE DISTANCE OF LIFT REQUIRED
- MANUFACTURERS INSTRUCTIONS MUST BE FOLLOWED TO AVOID DAMAGE TO THE TANK DURING OFF-LOADING AND PLACING IN THE EXCAVATION
- THE LOCATION MUST BE CAREFULLY CONSIDERED TO ALLOW SAFE ACCESS FOR INSTALLATION
- TANK LID HAS A MAXIMUM AXLE LOADING CAPACITY OF 2.5T (2500KGS)
- BOTH ACCESS POINTS IN THE LID MEASURE 508MMX508MM (20"X20")

VANTAGE POINT:

- INSTALLING A SIMPLE RAIN WATER STORAGE TANK COULD PROVIDE A FARM WITH SUFFICIENT WATER FOR LIVESTOCK DRINKERS AND THE WASHING DOWN OF FARMYARDS AND MACHINERY.

MAX CAPACITY	LENGTH	WIDTH	DEPTH	WEIGHT
1300G	3500MM (11'6")	1500MM (4'11")	1450MM (4'9")	3.7T
AXLE LOADING	LENGTH	WIDTH	DEPTH	WEIGHT
4T (4000KGS)	3500MM (11'6")	1500MM (4'11")	150MM (6")	1.4T

www.maxwellconcrete.co.uk