APEX WALLS

ENGAGING THE NEED FOR MOVEABILITY AND

DURABILITY









Maxwell Concrete
22 Folliard Road, Castlederg
Co Tyrone, BT81 7JW
T: 028 816 71326 F: 028 816 71736
Email: info@maxwellconcrete.co.uk

APEX WALLS

WE UNDERSTAND THE NEED FOR MANEUVERABILITY

GRAIN SHEDS

QUALITY:

DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 8110

DESIGN:

- TONGUE AND GROOVE CREATE ONE CONTINUAL WALL, INCREASING STRENGTH AS A UNIT
- APEX BASE HAS NOTCHED OUT FORK POINTS FOR MANEUVERABILITY
- BOLTING HOLES FOR SECURING PERMANENT WALLS TO THE GROUND

FINISH:

SMOOTH SURFACE FINISH MEANS THE WALLS ARE RESISTANT TO DIRT

TECHNICAL:

- WALLS ARE PRODUCED USING STANDARD PANELS 150MM (6") DEEP
- WALLS ARE PRODUCED USING STANDARD PANELS 2440MM (8') HIGH
- WALLS ARE PRODUCED USING STANDARD PANELS 3050 (10') HIGH

VANTAGE POINT:

- APEX WALLS CAN BE POSITIONED BY A ONE-MAN TEAM
- TONGUE AND GROOVE REDUCED SPILLAGES FROM ONE MATERIAL TO ANOTHER

Height (ft)	Height (mm)	Width	Panel Depth	Base Dimensions	Weight Per Apex Unit
8'	2440	4'	6"	4' x 4'	2.40
10'	3050	4'	6"	4' x 4'	3.15