AGRICULTURAL STOCK WALLS

EASY TO INSTALL, REMOVE AND REBUILD



Maxwell Concrete 22 Folliard Road, Castlederg Co Tyrone, BT81 7JW

T: 028 816 71326 F: 028 816 71736 Email: info@maxwellconcrete.co.uk

AGRICULTURAL STOCK WALLS

DURABLE, COST-EFFECTIVE CONSTRUCTION FOR YOUR

CATTLE SHEDS

QUALITY:

- DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 8110 AND BS 5502
- STRICT STRESSING ANALYSIS

DESIGN:

- EXTREMELY RESILIENT TO IMPACT FROM FARM EQUIPMENT & LIVESTOCK DUE TO ITS FLEXIBLE PROPERTIES
- NO CONCRETE FOUNDATION IS REQUIRED AS A RESULT NON-DEPENDANT ON WEATHER CONDITIONS
- SMOOTH FINISH REDUCES PLASTERING COSTS AND PROVIDES EASY CLEANING OF WALLS
- COMBINES EXCELLENT THERMAL PROPERTIES, FIRE PROTECTION AND SOUND REDUCTION
- SPEED & EASE OF CONSTRUCTION MEANS PANELS CAN EASILY BE INSTALLED, REMOVED AND REBUILT BY CUSTOMERS IN THE FUTURE IF REQUIRED

FINISH:

 SMOOTH SURFACE FINISH MEANS THE WALLS WILL BE RESISTANT TO DIRT AND EASILY CLEANED

TECHNICAL:

- PANELS SUPPORTED BY STANCHIONS & INSTALLED HORIZONTALLY ACROSS
 THE BAY WIDTH, PLACED EITHER ON THE FACE OR BETWEEN THE WEBS OF
 THE STANCHIONS.
- PANELS ARE PRODUCED STANDARD 100MM (4") DEEP
- PANELS ARE PRODUCED STANDARD 150MM (6") DEEP
- JOINTS MAY BE CLOSED USING RESIN BASED SEALANTS

VANTAGE POINT:

- FAST ERECTION, FLEXIBLE PROPERTIES AND ECONOMICAL IN TERMS OF PRODUCT PURPOSE
- * See below for engineers recommended spans

| DEPTH | LENGTH | HEIGHT (FT) | HEIGHT (MM) |
|------------|--------------------|-------------|---------------|
| 100mm (4") | Up to 4800mm (16') | 4' + 5' | 1200mm/1500mm |
| 150mm (6") | Up to 6100mm (20') | 4' + 5' | 1200mm/1500mm |