

# FAST FLOW TROUGHS

FOLLOWS THE SIMPLE RULE THAT WATER  
SHOULD BE CLEAN, FRESH AND

## READILY AVAILABLE



Maxwell  
Concrete

Maxwell Concrete  
22 Folliard Road, Castlederg  
Co Tyrone, BT81 7JW  
T: 028 816 71326 F: 028 816 71736  
Email: [info@maxwellconcrete.co.uk](mailto:info@maxwellconcrete.co.uk)

[www.maxwellconcrete.co.uk](http://www.maxwellconcrete.co.uk)

**NEW PRODUCT!** PORTABLE L-WALLS FOR EASY SILAGE FACE SET-UP & ACCESS

# FAST FLOW TROUGHS

MEETING THE NEEDS OF FARMERS FOR A DEPENDABLE  
EASILY MAINTAINED TROUGH THAT CAN DEAL WITH

## PEAK DEMANDS

**QUALITY:**

- DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 3445
- FIBER AND STEEL REINFORCED

**DESIGN:**

- RECTANGULAR SHAPE ALLOWS ‘LONG-LINE’ DRINKING AREAS OF UP TO TWELVE COWS AT ANY GIVEN TIME
- PROVIDE UNEQUALLED REFILL RATES OF UP TO 280 LITRES/MINUTE
- PIPE PROTECTION GIVES DEPENDABLE WATER SUPPLY
- EASILY DRAINED THROUGH 37MM < 30MM OUTLETS, ONE AT EACH END
- 190G AND 300G PRODUCED WITH NOTCHED OUT FORK POSITIONS
- 100G DRINKER IS ADEQUATE TO PROVIDE DRINKING WATER TO TWO PADDOCKS SIMULTANEOUSLY
- RATE OF WATER ENTERING THE PIPE IS REFLECTED IN THE RATE OF WATER ENTERING THE TROUGH
- USABLE IN HIGH AND LOW PRESSURE MAINS SUPPLY

**FINISH:**

- SMOOTH, TAPERED SURFACE REFLECTS THE BENEFITS OF EASY WATER MANAGEMENT

**TECHNICAL:**

- ALL TROUGHS ARE SUPPLIED WITH APPROPRIATE FITTINGS
- NOTCHED OUT FORK POSITIONS AVAILABLE IN THE 190G AND 300G

**VANTAGE POINT:**

- CONSISTENT, RELIABLE AND ACCOUNTABLE

CAPACITY	LENGTH	WIDTH	DRINKING HEIGHT	DRAINAGE OUTLET	WEIGHT
100G	1707mm (5’7”)	912mm (3’)	730mm (3’4”)	37mm < 30mm	.650
190G	2100mm (6’11”)	1250mm (4’1”)	825mm (2’8”)	37mm < 30mm	1.3
300G	2500mm (8’3”)	1370mm (4’6”)	825mm (2’8”)	37mm < 30mm	1.5

www.maxwellconcrete.co.uk