www.maxwellconcrete.co.uk

LIVESTOCK FLOORING

DESIGNED





Maxwell Concrete
22 Folliard Road, Castlederg
Co Tyrone, BT81 7JW
T: 028 816 71326 F: 028 816 71736
Email: info@maxwellconcrete.co.uk

LIVESTOCK FLOORING

BRUSH FINISH

AVAILABLE AS STANDARD THROUGHOUT THE RANGE

QUALITY:

• DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 5502 & IS 249

DESIGN:

- SLAT SURFACE OF 5½" PROVIDES MAXIMUM COMFORT FOR ANIMALS
- 40MM (1½") SPACING PRESENTS ADEQUATE OPENING FOR MANURE TO BE PUSHED THROUGH
- ALL PRODUCTS WITHIN THE FLOORING RANGE ARE MANUFACTURED 25.4MM (1") SHORTER IN LENGTH FOR EASY HOUSE REPLACEMENTS

FINISH:

- BRUSH FINISH AS STANDARD PROVIDES CATTLE WITH CONFIDENT FOOTING THUS REDUCING THE LIKELIHOOD OF INJURY DURING HOUSING
- SMOOTH, TAPERED SIDES PREVENT BUILD UP OF MANURE; ENSURING CATTLE ARE KEPT CLEAN
- SHARP EDGES ARE ROUNDED TO GIVE LIVESTOCK GREATER COMFORT

VANTAGE POINTS:

- BRUSH FINISH GIVES MAXIMUM FOOT HOLDING FOR LIVESTOCK
- WET-CAST PRODUCTION METHODS ENABLE US TO MANUFACTURE A SLAT WITH SMOOTH, TAPERED SIDES
- * Non Standard Precast available on order

WIDTH	PRODUCT	7′	7'6"	8′	8′6″	9′	9'6"	10′	10′6″	11′	12′	12′6″	13′	14',15' 16'
3′6″	SLAT	4T	*											
4′	SAFETY SLAT	4T	*											
5′	MANHOLE SLAB	10T	*											
3′6″	PASSAGE SLAB	6T/ 10T	*	6T/ 10T	*	6T/ 10T	*	6T/ 10T	*	6T/ 10T	6T/ 10T	*	6T/ 10T	*
3′11″	CUBICLE BASE	800kg	800kg	800kg	800kg	*	*	*	*	*	*	*	*	800kg
14" W X 12" D	BEAM (12"X14")	T6/m run	N/A											
HAMMER HEAD 8½"- 5½"	SINGLES 6" & 7½"	800kg	N/A	N/A	N/A	N/A	N/A							