

SILAGE BARRIER WALLS

FIND THE EASY SOLUTION TO ACCESSING YOUR

SILAGE FACE



Maxwell Concrete
22 Folliard Road, Castlederg
Co Tyrone, BT81 7JW
T: 028 816 71326 F: 028 816 71736
Email: info@maxwellconcrete.co.uk

www.maxwellconcrete.co.uk

NEW PRODUCT! SILAGE PIT PRESTRESSED PANELLING AVAILABLE IN 6" OR 8" DEEP

SILAGE BARRIER WALLS

TEMPORARY OR PERMANENT WHATEVER THE PURPOSE FREE STANDING

QUALITY:

- DESIGNED AND MANUFACTURED IN ACCORDANCE WITH BS 5502

DESIGN:

- NOTCHED OUT FORK POSITIONS PROVIDE EASE OF SILAGE FACE SET-UP
- CAST-IN TOWING SOCKETS ARE PROVIDED AT THE HEEL AS STANDARD TO ASSIST FARMERS WITH A STRAIGHTFORWARD METHOD OF ACCESSING THEIR SILAGE FACE
- ALL UNITS ARE DESIGNED TO ACCOMMODATE LOADING FROM EITHER SIDE OF THE WALL.

FINISH:

- SMOOTH SURFACE FINISH

TECHNICAL:

- ALL UNITS ARE DESIGNED TO TAKE A MAXIMUM SURCHARGE OF 10KN/M²
- UNITS ARE PRODUCED WITH UNIFORM WIDTH OF 1000MM (3'3")
- UNITS ARE PRODUCED WITH UNIFORM LENGTH OF 1700MM (5'7")
- THE UNITS REQUIRE A SUITABLE CONCRETE FOUNDATION THAT HAS BEEN DESIGNED BY A QUALIFIED ENGINEER TO ENSURE GROUND BEARING AND STABILITY REQUIREMENTS ARE MET.
- JOINTS MAY BE CLOSED USING RESIN BASED SEALANTS

VANTAGE POINT:

- SOLID, STABLE BARRIERS, TEMPORARY OR PERMANENT FOR WHATEVER PURPOSE
- APPROVED LIFTING ATTACHMENT AVAILABLE WITH YOUR L-WALL PURCHASE FOR SAFE AND FLEXIBLE TRANSPORTION AROUND YOUR FARM

(Please see front leaflet for illustration)

HEIGHT (MM)	HEIGHT (FT)	WIDTH (MM)	WIDTH (FT)	LENGTH (MM)	LENGTH (FT)	LOADING KG/TONNES	WEIGHT
2997MM	9'10"	1000MM	3'3"	1700MM	5'7"	10kN/m ²	1.6T
2387MM	7'10"	1000MM	3'3"	1700MM	5'7"	10kN/m ²	1.4T

www.maxwellconcrete.co.uk

NEW PRODUCT! FIELD DRINKERS 15G , 30G , 75G TO SUIT GRAZING OR HOUSING